

DS-2CC1132P(N)-IR



Key Features

- I Compact design
- I DIS
- I Min. illumination: 0.1 Lux @ F1.2 (0 Lux with IR)
- I **IR cut filter with auto switch**
- I Auto white balance, auto gain control, electronic shutter control and backlight compensation
- I Internal Synchronization
- I Advanced Engineering Design, High Reliability
- I **Weather proof rating: IP66**

Specification

Model	DS-2CC1132P(N)-IR
Parameter	500 TVL DIS ICR IR Weather-proof Bullet Camera
Camera	
Image Sensor	1/4" DIS
Signal System	PAL/NTSC
Effective Pixels	640 (H) × 480 (V)
Min. Illumination	0.1 Lux @ (F1.2, AGC ON), 0 Lux with IR 0.2Lux @ (F1.8, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/15,000 s NTSC: 1/30 s to 1/15,000 s
Lens	2.8 mm @ F1.8 (3.6 mm, 6 mm optional) Angle of view: 66.2° (2.8 mm)
Lens Mount	M12

Day & Night	IR cut filter with auto switch
Horizontal Resolution	500 TVL
Synchronization	Internal synchronization
Video Output	1Vp-p composite output (75 Ω/BNC)
S/N Ratio	More than 52 dB
BLC	On
General	
Operating Conditions	-40 °C - 70 °C (-40°F - 158 °F) Humidity 90% or less (non-condensing)
Power Supply	12 V DC ± 10%
Power Consumption	1 W (Max. 2.5 W with IR cut filter on)
Weather roof Rating	IP66
IR Range	Approx 10 to 20 meters
Dimension	Φ 65 × 104 mm (φ 2.56" × 4.09")
Weight	250 g (0.55 lbs)

Order Models

DS-2CC1132P-IR DS-2CC1132N-IR

Dimension

