



inBio-460 Pro

➔ Multidoor Access Control - 4 Door

Number of doors controller : 4 Door

Numbers of readers supported : 12 (8 RS-485 Reader, 4 26-bit wiegand reader)

Types of readers supported : 26-bit Wiegand & RS485 FR Series Reader

Number of Inputs : 12(4 Exit Device, 4 Door Status, 4 AUX)

Number of Outputs : 8 (4-Form C Relay or Lock & 4-Form C Relay for Aux Output)

Card holders Capacity : 30,000

Fingerprint Capacity : 3,000 (optional 20,000)

Log Events Capacity : 100,000

Communication : TCP/IP and RS-485

Package Dimension : 350(L)×90(H)×300(W)mm

Package Weight : 3.7kg

CPU : 32 bit 400MHz CPU

Features:

- ▶ Embedded Fingerprint verification and advance access control function
- ▶ It can be installed easily on your network also support TCP/IP and RS485 communication
- ▶ 1/2/4 Door models can be mixed and matched in an optimised System Architecture
- ▶ Data is preserved if power is lost, Controller continues to operate if data connection is interrupted
- ▶ Anti-Passback, First-Card Opening, Multi-Card Opening,
- ▶ Duress Password Entry, and Auxiliary input/output linkages are inbuilt into controller firmware

Connectivity Diagram

